PATENT ABSTRACTS OF JAPAN

(11)Publication number : 04-057821

(43)Date of publication of application : 25.02.1992

(51)Int.Cl.	C08G 59/30
	C08G 59/50
	C08J 5/24
	C08L 63/00
	// C08L 63:00

(21)Application number : 02-171070

(22)Date of filing : 28.06.1990

(71)Applicant : TORAY CHIOKOOLE KK

(72)Inventor : KURAMOTO HIROYOSHI

KATSUHATA KATSUHIKO

(54) EPOXY RESIN COMPOSITION FOR ARAMID FIBER PREPREG

(57)Abstract:

PURPOSE: To obtain the title composition which is highly flexible, tough and resistant to alkali and has good adhesion to aramid fiber or concrete by mixing a specified polysulfide-modified epoxy resin with an amine.

CONSTITUTION: A polysulfide-modified epoxy resin of formula I [wherein R1 and R3 are each an organic group having a bisphenol skeleton; R2 is a polysulfide skeleton of formula II (wherein (m) is 1-3 and represent an average content of S in the polysulfide skeleton; and (n) is 1-50 and represents an average content of the polysulfide skeletons per molecule)] is mixed with an amine (e.g. triethylenetetramine or m-xylenediamine) to obtain an epoxy resin composition for an aramid fiber prepreg having an elongation at break after being cured of 5% or above. This composition is highly flexible, tough and excellent in alkali resistance and has good adhesion to aramid fiber or concrete. This composition is suitable not only as a matrix of composite materials for civil engineering and construction such as a reinforcement for concrete but also as a matrix of composite materials for automobiles, ships and industry.

LEGAL STATUS

[Date of request for examination]

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's decision of rejection]

[Date of extinction of right]